

Package: EpiStats (via r-universe)

August 21, 2024

Type Package

Title Tools for Epidemiologists

Version 1.6-2

Date 2023-09-29

Description Provides set of functions aimed at epidemiologists. The package includes commands for measures of association and impact for case control studies and cohort studies. It may be particularly useful for outbreak investigations including univariable analysis and stratified analysis. The functions for cohort studies include the CS(), CStable() and CSInter() commands. The functions for case control studies include the CC(), CCTable() and CCInter() commands. References - Cornfield, J. 1956. A statistical problem arising from retrospective studies. In Vol. 4 of Proceedings of the Third Berkeley Symposium, ed. J. Neyman, 135-148. Berkeley, CA - University of California Press. Woolf, B. 1955. On estimating the relation between blood group disease. Annals of Human Genetics 19 251-253. Reprinted in Evolution of Epidemiologic Ideas Annotated Readings on Concepts and Methods, ed. S. Greenland, pp. 108-110. Newton Lower Falls, MA Epidemiology Resources. Gilles Desve & Peter Makary, 2007. 'CSTABLE Stata module to calculate summary table for cohort study' Statistical Software Components S456879, Boston College Department of Economics. Gilles Desve & Peter Makary, 2007. 'CCTABLE Stata module to calculate summary table for case-control study' Statistical Software Components S456878, Boston College Department of Economics.

License LGPL-3

Depends epiR, dplyr

Suggests knitr, rmarkdown

VignetteBuilder knitr

NeedsCompilation no

Author Jean Pierre Decorps [aut], Esther Kissling [ctb], Lore Merdrignac [cre]

Maintainer Lore Merdrignac <l.merdrignac@epiconcept.fr>

Date/Publication 2023-10-25 11:20:10 UTC

Repository <https://loremdrignac.r-universe.dev>

RemoteUrl <https://github.com/cran/EpiStats>

RemoteRef HEAD

RemoteSha e5b41196735e6c5b618abde34212d8955fe6f7b3

Contents

CC	2
CCInter	4
CCTable	6
crossTable	8
CS	9
CSInter	10
CSTable	12
orderFactors	14
Tiramisu	15
Index	17

CC *Univariate analysis of case control studies*

Description

CC is used with case-control studies to determine the association between an exposure and an outcome. Note that all variables need to be numeric and binary and coded as "0" and "1". Point estimates and confidence intervals for the odds ratio are calculated, along with attributable or prevented fractions for the exposed and total population.

Additionally you can select if you want to display the Fisher's exact test, by specifying `exact = TRUE`.

If you specify `full = TRUE` you can easily access useful statistics from the output tables.

Usage

```
CC(data, cases, exposure, exact = FALSE, full = FALSE, title = "CC")
```

Arguments

<code>data</code>	data.frame
<code>cases</code>	character - Case variable
<code>exposure</code>	character - Exposure variable
<code>exact</code>	boolean - TRUE if you would like to display Fisher's exact p-value
<code>full</code>	boolean - TRUE if you need to display useful statistics and values for formatting
<code>title</code>	character - title of tables

Value

list:

df1	data.frame - two by two table
df2	data.frame - statistics
df1.align	character - alignment for kable/xtable
df2.align	character - alignment for kable/xtable
df1.digits	integer vector - digit number displayed for kable/xtable
df2.digits	integer vector - digit number displayed for kable/xtable
st	list - individual statistics

The item `st` returns the odds ratio and its 95 percent confidence intervals, the attributable fraction among the exposed and its 95 percent confidence intervals, the attributable fraction among the population and its 95 percent confidence intervals, the Chi square value, the Chi square p-value and the Fisher's exact test p-value.

Note

You can use the lowercase command "cc" in place of "CC"

Please note also that when the outcome is frequent the odds ratio will overestimate the risk ratio (if $OR > 1$) or underestimate the risk ratio ($OR < 1$). If the outcome is rare, the risk ratio and the odds ratio are similar.

In a case control study, the attributable fraction among the exposed and among the population assume that the OR approximates the risk ratio.

Please interpret all measures with caution.

Author(s)

jean.pierre.decorps@gmail.com

References

Stata 13: cc <https://www.stata.com/manuals13/stepitab.pdf>

See Also

CCTable, CCInter, CS, CSTable, CSInter

Examples

```
library(EpiStats)

# Dataset by Anja Hauri, RKI.
data(Tiramisu)
DF <- Tiramisu

# The CC command looks at the association between the outcome variable "ill"
# and an exposure "mousse"
```

```

CC(DF, "ill", "mousse")

# The option exact = TRUE provides Fisher's exact test p-values
CC(DF, "ill", "mousse", exact = TRUE)

# With the option full = TRUE you can easily use individual elements of the results:
result <- CC(DF, "ill", "mousse", full = TRUE)
result$st$odds_ratio$point_estimate

```

CCInter

Stratified analysis for case control studies

Description

CCInter is useful to determine the effects of a third variable on the association between an exposure and an outcome. CCInter produces 2 by 2 tables with stratum specific odds ratios, attributable risk among exposed and population attributable risk.

Note that the outcome and exposure variable need to be numeric and binary and coded as "0" and "1". The third variable needs to be numeric, but may have more categories, such as "0", "1" and "2".

Usage

```
CCInter(x, cases, exposure, by, table = FALSE, full = FALSE)
```

Arguments

x	data.frame
cases	string: case binary variable (0 / 1)
exposure	string: exposure binary variable (0 / 1)
by	string: stratifying variable (a factor)
table	boolean - TRUE if you need to display interaction table
full	boolean - TRUE if you need to display useful values for formatting

Details

CCInter is useful to determine the effects of a third variable on the association between an exposure and an outcome. CCInter produces 2 by 2 tables with stratum specific odds ratios, attributable risk among exposed and population attributable risk. Note that the outcome and exposure variable need to be numeric and binary and coded as "0" and "1". The third variable needs to be numeric, but may have more categories, such as "0", "1" and "2". CCInter displays a summary with the crude OR, the Mantel Haenszel adjusted OR and the result of a Woolf test for homogeneity of stratum-specific OR.

The option "full = TRUE" provides you with useful formatting information, which can be handy if you're using "markdown".

Value

list:

df1	data.frame - cross-table
df2	data.frame - statistics
df1.digits	integer vector - digit number displayed for kable/xtable
df1.align	character - alignment for kable/xtable
df2.digits	integer vector - digit number displayed for kable/xtable
df2.align	character - alignment for kable/xtable

Note

- You can use lowercas command "ccinter" instead of "CCInter" - The "by" variable (the stratifying variable) can have more than 2 levels

Author(s)

jean.pierre.decorps@gmail.com

References

ccinter for Stata by *Gilles Desve*

See Also

CC, CCTable

Examples

```
library(EpiStats)

data(Tiramisu)
DF <- Tiramisu

# Here you can see the association between wmousse and ill for each stratum of tira:
CCInter(DF, "ill", "wmousse", by = "tira")

# By storing the results in the object "res", you can use individual elements of the results.
# For example if you would like to view just the Mantel-Haenszel odds ratio for beer adjusted
# for tportion, you can view it by typing:

res <- CCInter(DF, "ill", "beer", "tportion", full = TRUE)
res$df2$Stats[3]
```

CCTable

*Summary table for univariate analysis of case control studies***Description**

CCTable is used for univariate analysis of case control studies with several exposures. The results are summarised in one table with one row per exposure making comparisons between exposures easier and providing a useful table for integrating into reports. Note that all variables need to be numeric and binary and coded as "0" and "1".

The results of this function contain: The name of exposure variables, the total number of cases, the number of exposed cases, the percentage of exposed among cases, the number of controls, the number of exposed controls, the percentage of exposed among controls, odds ratios, 95%CI intervals, p-values.

You can optionally choose to display the Fisher's exact p-value instead of the Chi squared p-value, with the option `exact = TRUE`.

You can specify the sort order, with the option `sort = "or"` to order by odds ratios. The default sort order is by p-values.

The option `full = TRUE` provides you with useful formatting information, which can be handy if you're using "markdown".

Usage

```
CCTable(x, cases, exposure = c(), exact = FALSE, sort = "pvalue", full = FALSE)
```

Arguments

<code>x</code>	data.frame
<code>cases</code>	character - cases binary variable (0 / 1)
<code>exposure</code>	character vector - exposure variables
<code>exact</code>	boolean - TRUE if you want the Fisher's exact p-value instead of CHI2
<code>sort</code>	character - [pvalue, or, pe] sort by pvalue (default) or by odds ratio, or by percent exposed
<code>full</code>	boolean - TRUE if you need to display useful values for formatting

Details

The results of this function contain: The name of exposure variables, the total number of cases, the number of exposed cases, the percentage of exposed among cases, the number of controls, the number of exposed controls, the percentage of exposed among controls, odds ratios, 95%CI intervals, p-values.

You can optionally choose to display the Fisher's exact p-value instead of the Chi squared p-value, with the option `exact = TRUE`.

You can specify the sort order, with the option `sort="or"` to order by odds ratios. The default sort order is by p-values.

The option "full = TRUE" provides you with useful formatting information, which can be handy if you're using "markdown".

Value

list :

df	data.frame - results table
digits	integer vector - digit number displayed for kable/xtable
align	character - alignment for kable/xtable

Note

- You can use the lowercase command "cctable" instead of "CCTable"

Author(s)

jean.pierre.decorps@gmail.com

References

cctable for Stata by *Gilles Desve* and *Peter Makary*.

See Also

CC, CCInter

Examples

```
library(EpiStats)

data(Tiramisu)
df <- Tiramisu

# You can see the association between several exposures and being ill.
cctable(df, "ill", exposure=c("wmousse", "tira", "beer", "mousse"))

# By storing results in res, you can also use individual elements of the results.
# For example if you would like to view a particular odds ratio,
# you can view it by typing (for example):

res = CCTable(df, "ill", exposure = c("wmousse", "tira", "beer", "mousse"), exact=TRUE)
res$df$OR[1]
```

crossTable	<i>contingency table of 2 variables</i>
------------	---

Description

Creates a contingency table of 2 variables. Percentages are optional by row, column or both. It can provides an optional statistic (Fisher or Chisquare).

Usage

```
crossTable(data, var1, var2, percent="none", statistic="none")
```

Arguments

data	data.frame
var1	character - first varname - can be unquoted
var2	character - second varname - can be unquoted
percent	character - "none" (default) or ("row", "col", "both") - can be unquoted
statistic	character - "none" (default) or ("fisher", "chi2") - can be unquoted

Value

data.frame - contingency table

Author(s)

jean.pierre.decorps@gmail.com

See Also

orderFactors, CC, CS

Examples

```
library(EpiStats)

# Dataset by Anja Hauri, RKI.
data(Tiramisu)
DF <- Tiramisu

# Table with percentagges and statistic on ordered factors
DF %<>%
  orderFactors(ill , values = c(1,0), labels = c("YES", "NO")) %>%
  orderFactors(sex, values = c("males", "females"), labels = c("Males", "Females"))

crossTable(DF, "ill", "sex", "both", "chi2")
```


Description

CS analyses cohort studies with equal follow-up time per subject. The risk (the proportion of individuals who become cases) is calculated overall and among the exposed and unexposed. Note that all variables need to be numeric and binary and coded as "0" and "1".

Point estimates and confidence intervals for the risk ratio and risk difference are calculated, along with attributable or preventive fractions for the exposed and the total population.

Additionally you can select if you want to display the Fisher's exact test, by specifying `exact = TRUE`.

If you specify `full = TRUE` you can easily access useful statistics from the output tables.

Usage

```
CS(x, cases, exposure, exact = F, full = FALSE, title = "CS")
```

Arguments

<code>x</code>	data.frame
<code>cases</code>	character - Case variable
<code>exposure</code>	character - Exposure variable
<code>exact</code>	boolean - TRUE if you would like to display Fisher's exact p-value
<code>full</code>	boolean - TRUE if you need to display useful statistics and values for formatting
<code>title</code>	character - title of tables

Value

list:

<code>df1</code>	data.frame - two by two table
<code>df2</code>	data.frame - statistics
<code>st</code>	list - individual statistics
<code>df1.digits</code>	integer vector - digit number displayed for kable/xtable
<code>df2.digits</code>	integer vector - digit number displayed for kable/xtable
<code>df2.align</code>	character - alignment for kable/xtable

The item `st` returns the risk difference and its 95 percent confidence intervals, the risk ratio and its 95 percent confidence intervals, the attributable fraction among the exposed and its 95 percent confidence intervals, the attributable fraction among the population and its 95 percent confidence intervals, the Chi square value, the Chi square p-value and the Fisher's exact test p-value.

Note

You can use the lowercase command "cs" in place of "CS"

Author(s)

jean.pierre.decorps@gmail.com

References

Stata 13: cs. <https://www.stata.com/manuals13/stepitab.pdf>

See Also

CSTable, CSInter, CC, CCTable, CCInter

Examples

```
library(EpiStats)

# Dataset by Anja Hauri, RKI.
# Dataset provided with package.
data(Tiramisu)
DF <- Tiramisu

# The CS command looks at the association between the outcome variable "ill"
# and an exposure "mousse"
CS(DF, "ill", "mousse")

# The option exact = TRUE provides Fisher's exact test p-values
CS(DF, "ill", "mousse", exact = TRUE)

# With the option full = TRUE you can easily use individual elements of the results:
result <- CS(DF, "ill", "mousse", full = TRUE)
result$st$risk_ratio$point_estimate
```

CSInter

Stratified analysis for cohort studies measuring risk

Description

CSInter is useful to determine the effects of a third variable on the association between an exposure and an outcome. CSInter produces 2 by 2 tables with stratum specific risk ratios, attributable risk among exposed and population attributable risk. Note that the outcome and exposure variable need to be numeric and binary and coded as "0" and "1". The third variable needs to be numeric, but may have more categories, such as "0", "1" and "2".

Usage

```
CSInter(x, cases, exposure, by, table = FALSE, full = FALSE)
```

Arguments

x	data.frame
cases	string: illness binary variable (0 / 1)
exposure	string: exposure binary variable (0 / 1)
by	string: stratifying variable (a factor)
table	boolean - TRUE if you need to display interaction table
full	boolean - TRUE if you need to display useful values for formatting

Details

CSInter is useful to determine the effects of a third variable on the association between an exposure and an outcome. CSInter produces 2 by 2 tables with stratum specific risk ratios, attributable risk among exposed and population attributable risk. Note that the outcome and exposure variable need to be numeric and binary and coded as "0" and "1". The third variable needs to be numeric, but may have more categories, such as "0", "1" and "2".

CSInter displays a summary with the crude RR, the Mantel Haenszel adjusted RR and the result of a "Woolf" test for homogeneity of stratum-specific RR.

The option `full = TRUE` provides you with useful formatting information, which can be handy if you're using "markdown".

Value

list:

df1	data.frame - cross-table
df2	data.frame - statistics
df1.digits	integer vector - digit number displayed for kable/xtable
df2.digits	integer vector - digit number displayed for kable/xtable

Note

- You can use the lowercase command "csinter" instead of "CSInter" - The "by" variable (the stratifying variable) can have more than 2 levels

Author(s)

jean.pierre.decorps@gmail.com

References

csinter for Stata by *Gilles Desve*

See Also

CS, CSTable

Examples

```
library(EpiStats)

data(Tiramisu)
DF <- Tiramisu

# Here you can see the association between wmousse and ill for each stratum of tira:
csinter(DF, "ill", "wmousse", by = "tira")

# By storing the results in the object "res", you can use individual elements
# of the results. For example if you would like to view just the Mantel-Haenszel
# risk ratio for beer adjusted for tportion, you can view it by typing:
res <- CSInter(DF, "ill", "beer", "tportion", full = TRUE)
res$df2$Stats[3]
```

CSTable

Summary table for univariate analysis of cohort studies measuring risk

Description

CSTable is used for univariate analysis of cohort studies with several exposures. The results are summarised in one table with one row per exposure making comparisons between exposures easier and providing a useful table for integrating into reports. Note that all variables need to be numeric and binary and coded as "0" and "1".

The results of this function contain: The name of exposure variables, the total number of exposed, the number of exposed cases, the attack rate among the exposed, the total number of unexposed, the number of unexposed cases, the attack rate among the unexposed, risk ratios, 95% percent confidence intervals, and p-values.

You can optionally choose to display the Fisher's exact p-value instead of the Chi squared p-value, with the option `exact = TRUE`.

You can specify the sort order, with the option `sort="rr"` to order by risk ratios. The default sort order is by p-values.

The option `full = TRUE` provides you with useful formatting information, which can be handy if you're using "markdown".

Usage

```
CSTable(x, cases, exposure = c(), exact = FALSE, sort = "pvalue", full = FALSE)
```

Arguments

x	data.frame
cases	string - variable containing cases (binary 0 / 1)
exposure	string vector - names of variables containing exposure (binary 0 / 1)
exact	boolean - TRUE if you want the Fisher's exact p-value instead of CHI2
sort	character - [pvalue, rr, ar] sort by pvalue (default) or by risk ratio, or by percent of attributable risk
full	boolean - TRUE if you need to display useful values for formatting

Details

The results of this function contain: The name of exposure variables, the total number of exposed, the number of exposed cases, the attack rate among the exposed, the total number of unexposed, the number of unexposed cases, the attack rate among the unexposed, risk ratios, 95

You can optionally choose to display the Fisher's exact p-value instead of the Chi squared p-value, with the option `exact = TRUE`.

You can specify the sort order, with the option `sort="rr"` to order by risk ratios. The default sort order is by p-values.

The option `full = TRUE` provides you with useful formatting information, which can be handy if you're using "markdown".

Value

list :

df	data.frame - results table
digits	integer vector - digit number displayed for kable/xtable
align	character - alignment for kable/xtable

Note

- You can use the lowercase command "cstable" instead of "CSTable"

Author(s)

jean.pierre.decorps@gmail.com

References

cstable for Stata by *Gilles Desve* and *Peter Makary*

See Also

CS, CSInter

Examples

```
library(EpiStats)

data(Tiramisu)
df <- Tiramisu

# You can see the association between several exposures and being ill.
CSTable(df, "ill", exposure=c("wmousse", "tira", "beer", "mousse"))

# By storing results in res, you can also use individual elements of the results.
# For example if you would like to view a particular risk ratio,
# you can view it by typing (for example):
res <- CSTable(df, "ill", exposure = c("wmousse", "tira", "beer", "mousse"), exact=TRUE)
res$df$RR[1]
```

orderFactors	<i>Generates ordered factors.</i>
--------------	-----------------------------------

Description

Generates ordered factors for a list of columns by name or by index or range.

Usage

```
orderFactors(data, ..., values, labels=NULL)
```

Arguments

data	data.frame
...	character - first varname - can be unquoted
values	character - second varname - can be unquoted
labels	character - NULL (default) or ("row", "col", "both") - can be unquoted

Value

data.frame - contingency table

Author(s)

jean.pierre.decorps@gmail.com

See Also

crossTable

Examples

```

library(EpiStats)

# Dataset by Anja Hauri, RKI.
data(Tiramisu)
DF <- Tiramisu

# Table with percentagges and statistic on ordered factors
DF %<>%
  orderFactors(ill , values = c(1,0), labels = c("YES", "NO")) %>%
  orderFactors(sex, values = c("males", "females"), labels = c("Males", "Females"))
crossTable(DF, "ill", "sex", "both", "chi2")

```

Tiramisu

A foodborne disease outbreak dataset

Description

The dataset available with the EpiStats package is from an outbreak investigation carried out in Germany in 1998 by Anja Hauri, Robert Koch Institute.

Usage

```
data(Tiramisu)
```

Format

A data frame with 291 observations with the following 21 variables.

```

ill a numeric vector
dateonset a date
sex a factor with levels females males
age a numeric vector
tira a numeric vector
tportion a numeric vector
wmousse a numeric vector
dmousse a numeric vector
mousse a numeric vector
mportion a numeric vector
beer a numeric vector
uniquekey a numeric vector
redjelly a numeric vector
fruitsalad a numeric vector
tomato a numeric vector

```

mince a numeric vector
salmon a numeric vector
horseradish a numeric vector
chickenwin a numeric vector
roastbeef a numeric vector
pork a numeric vector

References

The dataset available with the EpiStats package is from an outbreak investigation carried out in Germany in 1998 by Anja Hauri, Robert Koch Institute. It is used in case studies by organisations including EPIET, ECDC and EpiConcept. It is provided with this package with Anja's permission.

Examples

```
data(Tiramisu)  
## maybe str(Tiramisu) ; plot(Tiramisu) ...
```


Index

* ~documentation

- CC, [2](#)
- CCInter, [4](#)
- CCTable, [6](#)
- crossTable, [8](#)
- CS, [9](#)
- CSInter, [10](#)
- CSTable, [12](#)
- orderFactors, [14](#)

* datasets

- Tiramisu, [15](#)

- CC, [2](#)
- cc (CC), [2](#)
- CCInter, [4](#)
- ccinter (CCInter), [4](#)
- CCTable, [6](#)
- cctable (CCTable), [6](#)
- crossTable, [8](#)
- CS, [9](#)
- cs (CS), [9](#)
- CSInter, [10](#)
- csinter (CSInter), [10](#)
- CSTable, [12](#)
- cstable (CSTable), [12](#)

- orderFactors, [14](#)

- Tiramisu, [15](#)